

Model Number	Max. Capacity (tons)	Schedule 80 Pipe Size
BEF-5HC-25	25	5"
BEF-5HC-50	50	5"
BEF-8HC-50	50	8"
BEF-8HC-80	80	8"
BEF-12HC-80	80	12"
BEF-12HC-110	110	12"
BEF-12HC-130	130	12"

THE CHART CAPACITIES ALLOWS FOR 75 TO 90 DEGREE BOTTOM RIGGING ANGLE											
NOTE: SOME SIZES MUST USE 60 DEGREE MINIMUM RIGGING ANGLE (ALLOWS FOR 75 DEGREE TO 90 DEGREE BOTTOM RIGGING)											
Consult The Caldwell Group Inc. for applications requiring loads, spans or rigging angles not shown in this chart. Rigging angles and span effect load capacity.											
WEIGHT INCLUDE (2) ENDCAPS WITH PIVOTING LINKS AND SCHEDULE 80 PIPE - DOES NOT INCLUDE SHACKLE WEIGHT OR TOP AND BOTTOM RIGGING											
CAPACITY TONS	6	8	10	12	16	20	24	28	32	36	40
5	30HC - 5 - 6	30HC - 5 - 8	30HC - 5 - 10	30HC - 5 - 12	30HC - 5 - 16	30HC - 5 - 20	30HC - 5 - 24	30HC - 5 - 28	30HC - 5 - 32	30HC - 5 - 36	30HC - 5 - 40
PIPE SIZE	5" SCH 80	5" SCH 80	5" SCH 80	5" SCH 80	5" SCH 80	5" SCH 80	5" SCH 80	5" SCH 80	5" SCH 80	5" SCH 80	5" SCH 80
END CAP MODEL	BEF-5HC-25	BEF-5HC-25	BEF-5HC-25	BEF-5HC-25	BEF-5HC-25	BEF-5HC-25	BEF-5HC-25	BEF-5HC-25	BEF-8HC-50	BEF-8HC-50	BEF-8HC-50
WGT.	360 LBS	400 LBS	440 LBS	490 LBS	570 LBS	650 LBS	730 LBS	820 LBS	1710 LBS	1890 LBS	2060 LBS
H.R. AT 45 DEGREES	60 IN	72 IN	84 IN	96 IN	120 IN	144 IN	168 IN	192 IN	224 IN	248 IN	272 IN
H.R. AT 60 DEGREES	86 IN	106 IN	128 IN	148 IN	192 IN	232 IN	274 IN	316 IN	364 IN	406 IN	446 IN
BOTTOM SHACKLE	13.5 TON BTAS	13.5 TON BTAS	13.5 TON BTAS	13.5 TON BTAS	13.5 TON BTAS	13.5 TON BTAS	13.5 TON BTAS	13.5 TON BTAS	25 TON BTAS	25 TON BTAS	25 TON BTAS
TOP SHACKLE	17 TON BTAS	17 TON BTAS	17 TON BTAS	17 TON BTAS	17 TON BTAS	17 TON BTAS	17 TON BTAS	17 TON BTAS	35 TON BTAS	35 TON BTAS	35 TON BTAS
10	30HC - 10 - 6	30HC - 10 - 8	30HC - 10 - 10	30HC - 10 - 12	30HC - 10 - 16	30HC - 10 - 20	30HC - 10 - 24	30HC - 10 - 28	30HC - 10 - 32	30HC - 10 - 36	30HC - 10 - 40
PIPE SIZE	5" SCH 80	5" SCH 80	5" SCH 80	5" SCH 80	5" SCH 80	5" SCH 80	5" SCH 80	5" SCH 80	8" SCH 80	8" SCH 80	8" SCH 80
END CAP MODEL	BEF-5HC-25	BEF-5HC-25	BEF-5HC-25	BEF-5HC-25	BEF-5HC-25	BEF-5HC-25	BEF-5HC-25	BEF-5HC-25	BEF-8HC-50	BEF-8HC-50	BEF-8HC-50
WGT.	360 LBS	400 LBS	440 LBS	490 LBS	570 LBS	650 LBS	730 LBS	820 LBS	1710 LBS	1890 LBS	2060 LBS
H.R. AT 45 DEGREES	60 IN	72 IN	84 IN	96 IN	120 IN	144 IN	168 IN	N/A	224 IN	248 IN	272 IN
H.R. AT 60 DEGREES	86 IN	106 IN	128 IN	148 IN	192 IN	232 IN	274 IN	316 IN	364 IN	406 IN	446 IN
BOTTOM SHACKLE	13.5 TON BTAS	13.5 TON BTAS	13.5 TON BTAS	13.5 TON BTAS	13.5 TON BTAS	13.5 TON BTAS	13.5 TON BTAS	13.5 TON BTAS	25 TON BTAS	25 TON BTAS	25 TON BTAS
TOP SHACKLE	17 TON BTAS	17 TON BTAS	17 TON BTAS	17 TON BTAS	17 TON BTAS	17 TON BTAS	17 TON BTAS	17 TON BTAS	35 TON BTAS	35 TON BTAS	35 TON BTAS
15	30HC - 15 - 6	30HC - 15 - 8	30HC - 15 - 10	30HC - 15 - 12	30HC - 15 - 16	30HC - 15 - 20	30HC - 15 - 24	30HC - 15 - 28	30HC - 15 - 32	30HC - 15 - 36	30HC - 15 - 40
PIPE SIZE	5" SCH 80	5" SCH 80	5" SCH 80	5" SCH 80	5" SCH 80	5" SCH 80	5" SCH 80	5" SCH 80	8" SCH 80	8" SCH 80	8" SCH 80
END CAP MODEL	BEF-5HC-25	BEF-5HC-25	BEF-5HC-25	BEF-5HC-25	BEF-5HC-25	BEF-5HC-25	BEF-5HC-25	BEF-8HC-50	BEF-8HC-50	BEF-8HC-50	BEF-8HC-50
WGT.	360 LBS	400 LBS	440 LBS	490 LBS	570 LBS	650 LBS	730 LBS	820 LBS	1710 LBS	1890 LBS	2060 LBS
H.R. AT 45 DEGREES	60 IN	72 IN	84 IN	96 IN	120 IN	N/A	N/A	200 IN	224 IN	248 IN	272 IN
H.R. AT 60 DEGREES	86 IN	106 IN	128 IN	148 IN	192 IN	232 IN	274 IN	324 IN	364 IN	406 IN	446 IN
BOTTOM SHACKLE	13.5 TON BTAS	13.5 TON BTAS	13.5 TON BTAS	13.5 TON BTAS	13.5 TON BTAS	13.5 TON BTAS	13.5 TON BTAS	25 TON BTAS	25 TON BTAS	25 TON BTAS	25 TON BTAS
TOP SHACKLE	17 TON BTAS	17 TON BTAS	17 TON BTAS	17 TON BTAS	17 TON BTAS	17 TON BTAS	17 TON BTAS	35 TON BTAS	35 TON BTAS	35 TON BTAS	35 TON BTAS
20	30HC - 20 - 6	30HC - 20 - 8	30HC - 20 - 10	30HC - 20 - 12	30HC - 20 - 16	30HC - 20 - 20	30HC - 20 - 24	30HC - 20 - 28	30HC - 20 - 32	30HC - 20 - 36	30HC - 20 - 40
PIPE SIZE	5" SCH 80	5" SCH 80	5" SCH 80	5" SCH 80	5" SCH 80	5" SCH 80	8" SCH 80	8" SCH 80	8" SCH 80	8" SCH 80	8" SCH 80
END CAP MODEL	BEF-5HC-25	BEF-5HC-25	BEF-5HC-25	BEF-5HC-25	BEF-5HC-25	BEF-5HC-25	BEF-8HC-50	BEF-8HC-50	BEF-8HC-50	BEF-8HC-50	BEF-8HC-50
WGT.	360 LBS	400 LBS	440 LBS	490 LBS	570 LBS	650 LBS	1370 LBS	1540 LBS	1710 LBS	1890 LBS	2060 LBS
H.R. AT 45 DEGREES	60 IN	72 IN	84 IN	96 IN	120 IN	N/A	N/A	176 IN	200 IN	224 IN	N/A
H.R. AT 60 DEGREES	86 IN	106 IN	128 IN	148 IN	192 IN	232 IN	282 IN	324 IN	364 IN	406 IN	446 IN
BOTTOM SHACKLE	13.5 TON BTAS	13.5 TON BTAS	13.5 TON BTAS	13.5 TON BTAS	13.5 TON BTAS	13.5 TON BTAS	25 TON BTAS	25 TON BTAS	25 TON BTAS	25 TON BTAS	25 TON BTAS
TOP SHACKLE	17 TON BTAS	17 TON BTAS	17 TON BTAS	17 TON BTAS	17 TON BTAS	17 TON BTAS	35 TON BTAS	35 TON BTAS	35 TON BTAS	35 TON BTAS	35 TON BTAS
25	30HC - 25 - 6	30HC - 25 - 8	30HC - 25 - 10	30HC - 25 - 12	30HC - 25 - 16	30HC - 25 - 20	30HC - 25 - 24	30HC - 25 - 28	30HC - 25 - 32	30HC - 25 - 36	30HC - 25 - 40
PIPE SIZE	5" SCH 80	5" SCH 80	5" SCH 80	5" SCH 80	5" SCH 80	5" SCH 80	8" SCH 80	8" SCH 80	8" SCH 80	8" SCH 80	8" SCH 80
END CAP MODEL	BEF-5HC-25	BEF-5HC-25	BEF-5HC-25	BEF-5HC-25	BEF-5HC-25	BEF-5HC-25	BEF-8HC-50	BEF-8HC-50	BEF-8HC-50	BEF-8HC-50	BEF-8HC-50
WGT.	360 LBS	400 LBS	440 LBS	490 LBS	570 LBS	650 LBS	1190 LBS	1370 LBS	1540 LBS	1710 LBS	2060 LBS
H.R. AT 45 DEGREES	60 IN	72 IN	84 IN	N/A	N/A	152 IN	176 IN	200 IN	224 IN	N/A	N/A
H.R. AT 60 DEGREES	86 IN	106 IN	128 IN	148 IN	192 IN	240 IN	282 IN	324 IN	364 IN	406 IN	446 IN
BOTTOM SHACKLE	13.5 TON BTAS	13.5 TON BTAS	13.5 TON BTAS	13.5 TON BTAS	13.5 TON BTAS	25 TON BTAS	25 TON BTAS	25 TON BTAS	25 TON BTAS	25 TON BTAS	25 TON BTAS
TOP SHACKLE	17 TON BTAS	17 TON BTAS	17 TON BTAS	17 TON BTAS	17 TON BTAS	35 TON BTAS	35 TON BTAS	35 TON BTAS	35 TON BTAS	35 TON BTAS	35 TON BTAS
30	30HC - 30 - 6	30HC - 30 - 8	30HC - 30 - 10	30HC - 30 - 12	30HC - 30 - 16	30HC - 30 - 20	30HC - 30 - 24	30HC - 30 - 28	30HC - 30 - 32	30HC - 30 - 36	30HC - 30 - 40
PIPE SIZE	5" SCH 80	5" SCH 80	5" SCH 80	5" SCH 80	5" SCH 80	8" SCH 80	8" SCH 80	8" SCH 80	8" SCH 80	8" SCH 80	12" SCH 80
END CAP MODEL	BEF-5HC-50	BEF-5HC-50	BEF-5HC-50	BEF-5HC-50	BEF-8HC-50	BEF-8HC-50	BEF-8HC-50	BEF-8HC-50	BEF-8HC-50	BEF-8HC-50	BEF-12HC-80
WGT.	420 LBS	460 LBS	500 LBS	550 LBS	1020 LBS	1190 LBS	1370 LBS	1540 LBS	1710 LBS	1890 LBS	4100 LBS
H.R. AT 45 DEGREES	68 IN	N/A	N/A	N/A	128 IN	152 IN	176 IN	200 IN	224 IN	248 IN	278 IN
H.R. AT 60 DEGREES	94 IN	114 IN	136 IN	156 IN	200 IN	240 IN	282 IN	324 IN	364 IN	406 IN	452 IN
BOTTOM SHACKLE	25 TON BTAS	25 TON BTAS	25 TON BTAS	25 TON BTAS	25 TON BTAS	25 TON BTAS	25 TON BTAS	25 TON BTAS	25 TON BTAS	25 TON BTAS	55 TON BTAS
TOP SHACKLE	35 TON BTAS	35 TON BTAS	35 TON BTAS	35 TON BTAS	35 TON BTAS	35 TON BTAS	35 TON BTAS	35 TON BTAS	35 TON BTAS	35 TON BTAS	55 TON BTAS
40	30HC - 40 - 6	30HC - 40 - 8	30HC - 40 - 10	30HC - 40 - 12	30HC - 40 - 16	30HC - 40 - 20	30HC - 40 - 24	30HC - 40 - 28	30HC - 40 - 32	30HC - 40 - 36	30HC - 40 - 40
PIPE SIZE	5" SCH 80	5" SCH 80	5" SCH 80	5" SCH 80	5" SCH 80	8" SCH 80	8" SCH 80	8" SCH 80	8" SCH 80	12" SCH 80	12" SCH 80
END CAP MODEL	BEF-5HC-50	BEF-5HC-50	BEF-8HC-50	BEF-8HC-50	BEF-8HC-50	BEF-8HC-50	BEF-8HC-50	BEF-8HC-50	BEF-8HC-50	BEF-12HC-80	BEF-12HC-80
WGT.	420 LBS	460 LBS	760 LBS	850 LBS	1020 LBS	1190 LBS	1370 LBS	1540 LBS	1710 LBS	3750 LBS	4100 LBS
H.R. AT 45 DEGREES	N/A	N/A	92 IN	104 IN	128 IN	152 IN	176 IN	N/A	254 IN	N/A	278 IN
H.R. AT 60 DEGREES	94 IN	114 IN	136 IN	156 IN	200 IN	240 IN	282 IN	324 IN	364 IN	412 IN	452 IN
BOTTOM SHACKLE	25 TON BTAS	25 TON BTAS	25 TON BTAS	25 TON BTAS	25 TON BTAS	25 TON BTAS	25 TON BTAS	25 TON BTAS	25 TON BTAS	55 TON BTAS	55 TON BTAS
TOP SHACKLE	35 TON BTAS	35 TON BTAS	35 TON BTAS	35 TON BTAS	35 TON BTAS	35 TON BTAS	35 TON BTAS	35 TON BTAS	35 TON BTAS	55 TON BTAS	55 TON BTAS
50	30HC - 50 - 6	30HC - 50 - 8	30HC - 50 - 10	30HC - 50 - 12	30HC - 50 - 16	30HC - 50 - 20	30HC - 50 - 24	30HC - 50 - 28	30HC - 50 - 32	30HC - 50 - 36	30HC - 50 - 40
PIPE SIZE	5" SCH 80	5" SCH 80	8" SCH 80	8" SCH 80	8" SCH 80	8" SCH 80	8" SCH 80	8" SCH 80	8" SCH 80	12" SCH 80	12" SCH 80
END CAP MODEL	BEF-5HC-50	BEF-5HC-50	BEF-8HC-50	BEF-8HC-50	BEF-8HC-50	BEF-8HC-50	BEF-8HC-50	BEF-8HC-50	BEF-8HC-50	BEF-12HC-80	BEF-12HC-80
WGT.	420 LBS	460 LBS	760 LBS	850 LBS	1020 LBS	1190 LBS	1370 LBS	1540 LBS	1710 LBS	3750 LBS	4100 LBS
H.R. AT 45 DEGREES	N/A	N/A	92 IN	104 IN	128 IN	152 IN	176 IN	N/A	254 IN	N/A	278 IN
H.R. AT 60 DEGREES	94 IN	114 IN	136 IN	156 IN	200 IN	240 IN	282 IN	324 IN	364 IN	412 IN	452 IN
BOTTOM SHACKLE	25 TON BTAS	25 TON BTAS	25 TON BTAS	25 TON BTAS	25 TON BTAS	25 TON BTAS	25 TON BTAS	25 TON BTAS	25 TON BTAS	55 TON BTAS	55 TON BTAS
TOP SHACKLE	35 TON BTAS	35 TON BTAS	35 TON BTAS	35 TON BTAS	35 TON BTAS	35 TON BTAS	35 TON BTAS	35 TON BTAS	35 TON BTAS	55 TON BTAS	55 TON BTAS

THE CHART CAPACITIES ALLOWS FOR 75 TO 90 DEGREE BOTTOM RIGGING ANGLE											
NOTE: SOME SIZES MUST USE 60 DEGREE MINIMUM RIGGING ANGLE (ALLOWS FOR 75 DEGREE TO 90 DEGREE BOTTOM RIGGING)											
Consult The Caldwell Group Inc. for applications requiring loads, spans or rigging angles not shown in this chart. Rigging angles and span effect load capacity.											
WEIGHT INCLUDE (2) ENDCAPS WITH PIVOTING LINKS AND SCHEDULE 80 PIPE - DOES NOT INCLUDE SHACKLE WEIGHT OR TOP AND BOTTOM RIGGING											
CAPACITY TONS	6	8	10	12	16	20	24	28	32	36	40
60 PIPE SIZE END CAP MODEL WGT. H.R. AT 45 DEGREES H.R. AT 60 DEGREES BOTTOM SHACKLE TOP SHACKLE		30HC - 60 - 8 8" SCH 80 BEF-8HC-80 840 LBS 84 IN 120 IN	30HC - 60 - 10 8" SCH 80 BEF-8HC-80 920 LBS 96 IN 140 IN	30HC - 60 - 12 8" SCH 80 BEF-8HC-80 1010 LBS 108 IN 162 IN	30HC - 60 - 16 8" SCH 80 BEF-8HC-80 1190 LBS 132 IN 204 IN	30HC - 60 - 20 8" SCH 80 BEF-8HC-80 1360 LBS 156 IN 246 IN	30HC - 60 - 24 8" SCH 80 BEF-8HC-80 1530 LBS 180 IN 286 IN	30HC - 60 - 28 8" SCH 80 BEF-8HC-80 1710 LBS 204 IN 328 IN	30HC - 60 - 32 8" SCH 80 BEF-8HC-80 1880 LBS 230 IN 370 IN	30HC - 60 - 36 12" SCH 80 BEF-12HC-80 2180 LBS 254 IN 412 IN	30HC - 60 - 40 12" SCH 80 BEF-12HC-80 2410 LBS 278 IN 452 IN
70 PIPE SIZE END CAP MODEL WGT. H.R. AT 45 DEGREES H.R. AT 60 DEGREES BOTTOM SHACKLE TOP SHACKLE		30HC - 70 - 8 8" SCH 80 BEF-8HC-80 840 LBS 84 IN 120 IN	30HC - 70 - 10 8" SCH 80 BEF-8HC-80 920 LBS 96 IN 140 IN	30HC - 70 - 12 8" SCH 80 BEF-8HC-80 1010 LBS 108 IN 162 IN	30HC - 70 - 16 8" SCH 80 BEF-8HC-80 1190 LBS 132 IN 204 IN	30HC - 70 - 20 12" SCH 80 BEF-12HC-80 2330 LBS 156 IN 246 IN	30HC - 70 - 24 12" SCH 80 BEF-12HC-80 2690 LBS 180 IN 286 IN	30HC - 70 - 28 12" SCH 80 BEF-12HC-80 3040 LBS 204 IN 328 IN	30HC - 70 - 32 12" SCH 80 BEF-12HC-80 3400 LBS 230 IN 370 IN	30HC - 70 - 36 12" SCH 80 BEF-12HC-80 3750 LBS 254 IN 412 IN	30HC - 70 - 40 12" SCH 80 BEF-12HC-80 4100 LBS 278 IN 452 IN
80 PIPE SIZE END CAP MODEL WGT. H.R. AT 45 DEGREES H.R. AT 60 DEGREES BOTTOM SHACKLE TOP SHACKLE		30HC - 80 - 8 8" SCH 80 BEF-8HC-80 840 LBS 84 IN 120 IN	30HC - 80 - 10 8" SCH 80 BEF-8HC-80 920 LBS 96 IN 140 IN	30HC - 80 - 12 8" SCH 80 BEF-8HC-80 1010 LBS 108 IN 162 IN	30HC - 80 - 16 8" SCH 80 BEF-8HC-80 1190 LBS 132 IN 204 IN	30HC - 80 - 20 12" SCH 80 BEF-12HC-80 2330 LBS 156 IN 246 IN	30HC - 80 - 24 12" SCH 80 BEF-12HC-80 2690 LBS 180 IN 286 IN	30HC - 80 - 28 12" SCH 80 BEF-12HC-80 3040 LBS 204 IN 328 IN	30HC - 80 - 32 12" SCH 80 BEF-12HC-80 3400 LBS 230 IN 370 IN	30HC - 80 - 36 12" SCH 80 BEF-12HC-80 3750 LBS 254 IN 412 IN	30HC - 80 - 40 12" SCH 80 BEF-12HC-80 4100 LBS 278 IN 452 IN
90 PIPE SIZE END CAP MODEL WGT. H.R. AT 45 DEGREES H.R. AT 60 DEGREES BOTTOM SHACKLE TOP SHACKLE		30HC - 90 - 8 12" SCH 80 BEF-12HC-110 1420 LBS 84 IN 120 IN	30HC - 90 - 10 12" SCH 80 BEF-12HC-110 1600 LBS 96 IN 140 IN	30HC - 90 - 12 12" SCH 80 BEF-12HC-110 1780 LBS 108 IN 162 IN	30HC - 90 - 16 12" SCH 80 BEF-12HC-110 2130 LBS 132 IN 204 IN	30HC - 90 - 20 12" SCH 80 BEF-12HC-110 2490 LBS 156 IN 246 IN	30HC - 90 - 24 12" SCH 80 BEF-12HC-110 2840 LBS 180 IN 286 IN	30HC - 90 - 28 12" SCH 80 BEF-12HC-110 3200 LBS 204 IN 328 IN	30HC - 90 - 32 12" SCH 80 BEF-12HC-110 3550 LBS 230 IN 370 IN	30HC - 90 - 36 12" SCH 80 BEF-12HC-110 3900 LBS 254 IN 412 IN	30HC - 90 - 40 12" SCH 80 BEF-12HC-110 4260 LBS 278 IN 452 IN
100 PIPE SIZE END CAP MODEL WGT. H.R. AT 45 DEGREES H.R. AT 60 DEGREES BOTTOM SHACKLE TOP SHACKLE		30HC - 100 - 8 12" SCH 80 BEF-12HC-110 1420 LBS 84 IN 120 IN	30HC - 100 - 10 12" SCH 80 BEF-12HC-110 1600 LBS 96 IN 140 IN	30HC - 100 - 12 12" SCH 80 BEF-12HC-110 1780 LBS 108 IN 162 IN	30HC - 100 - 16 12" SCH 80 BEF-12HC-110 2130 LBS 132 IN 204 IN	30HC - 100 - 20 12" SCH 80 BEF-12HC-110 2490 LBS 156 IN 246 IN	30HC - 100 - 24 12" SCH 80 BEF-12HC-110 2840 LBS 180 IN 286 IN	30HC - 100 - 28 12" SCH 80 BEF-12HC-110 3200 LBS 204 IN 328 IN	30HC - 100 - 32 12" SCH 80 BEF-12HC-110 3550 LBS 230 IN 370 IN	30HC - 100 - 36 12" SCH 80 BEF-12HC-110 3900 LBS 254 IN 412 IN	30HC - 100 - 40 12" SCH 80 BEF-12HC-110 4260 LBS 278 IN 452 IN
110 PIPE SIZE END CAP MODEL WGT. H.R. AT 45 DEGREES H.R. AT 60 DEGREES BOTTOM SHACKLE TOP SHACKLE		30HC - 110 - 8 12" SCH 80 BEF-12HC-110 1420 LBS 84 IN 120 IN	30HC - 110 - 10 12" SCH 80 BEF-12HC-110 1600 LBS 96 IN 140 IN	30HC - 110 - 12 12" SCH 80 BEF-12HC-110 1780 LBS 108 IN 162 IN	30HC - 110 - 16 12" SCH 80 BEF-12HC-110 2130 LBS 132 IN 204 IN	30HC - 110 - 20 12" SCH 80 BEF-12HC-110 2490 LBS 156 IN 246 IN	30HC - 110 - 24 12" SCH 80 BEF-12HC-110 2840 LBS 180 IN 286 IN	30HC - 110 - 28 12" SCH 80 BEF-12HC-110 3200 LBS 204 IN 328 IN	30HC - 110 - 32 12" SCH 80 BEF-12HC-110 3550 LBS 230 IN 370 IN	30HC - 110 - 36 12" SCH 80 BEF-12HC-110 3900 LBS 254 IN 412 IN	30HC - 110 - 40 12" SCH 80 BEF-12HC-110 4260 LBS 278 IN 452 IN
120 PIPE SIZE END CAP MODEL WGT. H.R. AT 45 DEGREES H.R. AT 60 DEGREES BOTTOM SHACKLE TOP SHACKLE		30HC - 120 - 8 12" SCH 80 BEF-12HC-130 1450 LBS 96 IN 130 IN	30HC - 120 - 10 12" SCH 80 BEF-12HC-130 1620 LBS 108 IN 152 IN	30HC - 120 - 12 12" SCH 80 BEF-12HC-130 1800 LBS 120 IN 172 IN	30HC - 120 - 16 12" SCH 80 BEF-12HC-130 2150 LBS 144 IN 216 IN	30HC - 120 - 20 12" SCH 80 BEF-12HC-130 2500 LBS 168 IN 256 IN	30HC - 120 - 24 12" SCH 80 BEF-12HC-130 2860 LBS 192 IN 298 IN	30HC - 120 - 28 12" SCH 80 BEF-12HC-130 3220 LBS 216 IN 340 IN	30HC - 120 - 32 12" SCH 80 BEF-12HC-130 3570 LBS 240 IN 380 IN	30HC - 120 - 36 12" SCH 80 BEF-12HC-130 3920 LBS 264 IN 422 IN	30HC - 120 - 40 12" SCH 80 BEF-12HC-130 4280 LBS 288 IN 462 IN
130 PIPE SIZE END CAP MODEL WGT. H.R. AT 45 DEGREES H.R. AT 60 DEGREES BOTTOM SHACKLE TOP SHACKLE		30HC - 130 - 8 12" SCH 80 BEF-12HC-130 1450 LBS 96 IN 130 IN	30HC - 130 - 10 12" SCH 80 BEF-12HC-130 1620 LBS 108 IN 152 IN	30HC - 130 - 12 12" SCH 80 BEF-12HC-130 1800 LBS 120 IN 172 IN	30HC - 130 - 16 12" SCH 80 BEF-12HC-130 2150 LBS 144 IN 216 IN	30HC - 130 - 20 12" SCH 80 BEF-12HC-130 2500 LBS 168 IN 256 IN	30HC - 130 - 24 12" SCH 80 BEF-12HC-130 2860 LBS 192 IN 298 IN	30HC - 130 - 28 12" SCH 80 BEF-12HC-130 3220 LBS 216 IN 340 IN	30HC - 130 - 32 12" SCH 80 BEF-12HC-130 3570 LBS 240 IN 380 IN	30HC - 130 - 36 12" SCH 80 BEF-12HC-130 3920 LBS 264 IN 422 IN	30HC - 130 - 40 12" SCH 80 BEF-12HC-130 4280 LBS 288 IN 462 IN